


High Pressure Resistant

5YR  
Warranty



MODEL 15W-L10-230V-G DATA SHEET  
GREEN LED STRIP WITH SILICONE EXTRUSION



iluminaTronics

20 CABLE TIES



20 ISOLATING CLIPS



AC CONNECTOR



10 m roll



LED STRIP KIT  
MODEL 15W-L10-230V-G

ISOLATING FUSE





# GREEN LED STRIP SPECIFICATIONS

## MODEL 15W-L10-230V-G


GREEN LED STRIP DATA	MODEL: 15W-L10-230V-G
ELECTRICAL	
Input voltage	230 VAC 50/60 Hz
Supply voltage range	200 to 260 VAC 50/60 Hz
Current draw	0.7 A
Power factor (PF)	0.9
Power consumption per meter	15 W/m
Total set power	150 W
LED density	144 LEDs/m
LED package type	SMD 2835
PHOTOMETRICS	
Illuminance at 4 m mounting height	60-70 lux
Luminous flux (lm)	Varies
Correlated color temperature (CCT)	CCT = G (green)
Color rendering index (CRI)	Varies
Beam angle	120°
Photometric files	IES file
TEMPERATURE AND OPERATING CONDITIONS	
Ambient operating temperature	-45°C to +50°C
Maximum test-point temperature	75°C
SERVICE LIFE	
Typical service life	>5 years
Service life in 24/7 operation	3 years
Rated LED strip life	>50,000 h
Estimated maintenance savings	>20% per year
CERTIFICATIONS AND STANDARDS	
Compliance markings	CE / TÜV / ROHS / NOM
LED strip ingress protection	IP68
Connector ingress protection	IP68
Connectors	Factory-fitted
Outer jacket	Halogen-free food-grade silicone
Flame-retardant	Yes
Overvoltage protection	Yes
Overtemperature protection	Yes
Isolator fuse	Yes
Compression resistance	Yes
Tensile strength	50 kg



# GREEN LED STRIP SPECIFICATIONS

## MODEL 15W-L10-230V-G

GREEN LED STRIP DATA	MODEL: 15W-L10-230V-G
PRODUCT DIMENSIONS	
Length	10 m roll
Connection configuration	Individual 10 m sections or linkable up to 50 m in series
LED strip dimensions	4 mm high x 14 mm wide
Cable cross-section	2 x 1 mm
Cable voltage rating	300/500 V
Weight per 10 m roll	1.35 kg
Included mounting accessories	Yes
LOGISTICS	
LED strip part number	15W-L10-230V-G
Master carton contents	10 rolls of 10 m
Box dimensions (length x width x height)	40 x 40 x 30 cm
Gross box weight	14 kg
Volume	0.048 m <sup>3</sup>
Unit packaging	PVC zip bags
Master carton packaging	Cardboard box wrapped with stretch film





iluminaTronics



**5YR**  
Warranty



[www.iluminatronics.com](http://www.iluminatronics.com)  
United States of America

1211 San Dario Ave. #2068, Laredo, TX 78040 USA  
[sales@iluminatronics.com](mailto:sales@iluminatronics.com)  
Tel. USA: +1-941-893-2696

